



LPI® Fibreglass Reinforced Pole – FRP-2M & FRP-3M

- **Product Description** Ống sợi thủy tinh cách điện LPI FRP-2M

As a key component of the LPI lightning protection system, the FRP (Fibreglass reinforced pole) mast is an insulated and water resistant mounting pole which is designed to provide the necessary electrical isolation and mounting strength at the position where the high voltage upper termination between the HVSC (High Voltage Shielded Cable) downconductor and LPI lightning terminal is completed.

- **Technical Data**

Application:
Ordering code:
Dimensions:
FRP-2M:

FRP-3M:

Colour:
Weight:
Material:
Construction Type:

Electrical Properties:
Resin Tensile Strength:
Resin Tensile Modulus:
Resin Tensile Strain:
Resin Poisson Ratio:



Mounting Mast
FRP-2M, FRP-3M

Length 2000mm, Outer diameter 68mm, Inner diameter 60mm

Length 3000mm, Outer diameter 68mm, Inner diameter 60mm

Black
FRP-2M 2.7kg, FRP-3M 4kg
Fibreglass
Pre-impregnated Reinforced Epoxy Resin
Laminate (Flame Retardant)
Non Conductive

70 MPa
2.9 GPa
2.7%
0.35

- **Warranty**

This product is guaranteed to be free from materials and workmanship defects for a period of 2 years from the date of shipment from the manufacturer. This warranty does not offer any cover for consequential damage, loss of operation or loss of profit.



- **“LPI Endorsed Product”** – The symbol of assurance of quality and performance.
- LPI has a policy of continuing product development. Therefore, the above specifications are subject to change without notice.

LPI® - Innovative Lightning and Surge Protection Solutions



Direct Strike Protection



Surge & Transient Protection for Power, Data, Communications and RF lines



Grounding Products & Solutions